

CARVER S.r.l.
Via Giovanni XXIII, 36
20090 Rodano (MI) ITALY
Tel. (02) 95.00171 (r.a.)
Fax (02) 95.320.921
internet: www.carver.it



AZIENDA CON SISTEMA DI GESTIONE
AMBIENTALE CERTIFICATO DA DNV
= UNI EN ISO 14001:2004 =

AZIENDA CON SISTEMA DI GESTIONE
PER LA QUALITÀ CERTIFICATO DA DNV
= UNI EN ISO 9001:2008 =

TECHNICAL DATA SHEET

rev. 00 of 21st January, 2010

IDROVISC (thickening additive)

code SO1200

TECHNICAL DATA

(based on room temperature of +23°C and 65% of relative air humidity)

Appearance	opalescent liquid
Colour	whitish
Addition ratio	0.5 – 5.0 %
Viscosity	15" F8 ± 5" F8
Specific weight	1.02 ± 0.01
VOC (volatile organic compounds)	12.5% ±0.5%

DESCRIPTION

Additive for increasing the viscosity of water-based primers and finishes.

PACKAGING

1.0-litre bottle
0.2-litre bottle

DIRECTIONS

Pour the IDROVISC additive into the product to be thickened and mix thoroughly until fully dissolved. Wait 10 - 15 minutes, then apply.

Because each product reacts differently to the addition of IDROVISC, dosing should be determined on a case by case basis.

NOTICE

- This additive is not compatible with solvent-based systems .
- Too much IDROVISC may compromise the performances of the thickened product, such as flow or chemical and mechanical resistance. It may also increase the opacity or blooming of the dried surface film.
- When used in bi-component systems, please note that pot life could be reduced.
- IDROVISC is hydrophilic and if used in excessive quantities will reduce the water-repellency of the dried surface film.

Protect from freezing!

Dispose of excess product and empty containers properly.

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

N.B. The information contained in this technical data sheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.