

TECHNICAL DATASHEET

rev. 01 of 02/07/2004

BASICOL

code SO3060

TECHNICAL DATA

(based on room temperature of +23°C and 65% of relative air humidity)

Appearance	light brown paste
Viscosity	800 Poise
Specific weight	1,45 ± 0,01
Open time	15-20 mins
Foot traffic on the glued floor after	24 hrs
Complete drying	7 days
Average yield	1,0 - 1,4 m ² /kg

DESCRIPTION

One-face glue in acrylic dispersion, for gluing linoleum and vinyl-back floors on cement and absorbent subfloors.

Packaging: 21-kg plastic pail.

DIRECTIONS

Subfloor must be sound, not crumbling nor pulverizing, free from grease and old glue residues. Remove dust which there may be then spread the glue with a serrated spatula on the subfloor and lay the floor within 15-20 mins (good aeration and low relative humidity conditions shorten open time).

NOTICE

- We recommend to apply at a room temperature between +10°C and 30°C. Allow product to reach room temperature before application.
- During application protect your hands with rubber gloves or a barrier cream.
- Wet glue residuals can be removed with a moistened cloth.
- Use warm water to clean tools.
- If necessary, thin the product with lukewarm water.

Protect from freezing!

Dispose of excess product and empty containers properly.

If the original unopened container is stored at a temperature not below +5°C and not over +25°C, the product will keep for at least 9 months.

The information contained in this technical datasheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.