

TECHNICAL LEAFLET

18/3/97

DILUENTE M - 25

code SO1330

TECHNICAL DATA

Appearance	colourless transparent liquid
Viscosity	11" Ford cup 4
Specific weight	0,89
(the data above refer to a room temperature of +20°C and to a 65% of humidity)	

DESCRIPTION

Additive for parquet solvent base varnishes (varnishes with acid catalyst and mono- or bicomponent polyurethane varnishes), which avoids cissings, dewettings and other kinds of superficial faults, due to the presence in the room or on the to-be-varnished surface of silicone products or greasy substances, such as sealers, detaching agents, etc.

APPLICATION

Add DILUENTE M-25 in a ratio of 5 - 10% to the catalyzed varnish and mix very well. Then follow the provided varnish descriptions for use.

It is advisable to add DILUENTE M-25 to the last coat only.

In much smaller proportions (0,5% at the most) DILUENTE M-25 can be used also to improve the varnish spreading power and to avoid blistering.

USEFUL ADVICE

DILUENTE M-25 cannot eliminate all the faults and *should be used only when really necessary without exceeding in quantity*, or else problems could come about. For instance, when added to mat varnishes in greater quantity, DILUENTE M-25 may cause a loss of opacity and aesthetical faults.

In all doubtful cases it is recommended to have a preliminary test on a small area of the floor.

Do not throw any residual on ground or down drains!

If stored cool and dry, in the original unopened package, the product keeps at least 12 months.

NB. The information given in this technical leaflet springs from our knowledge and experience, but no guarantee can be given due to the wide range of uses and applications.