

TECHNICAL LEAFLET

rev. 00 2/6/99

PARQUET FIX

code SO7520

TECHNICAL DATA (with room temperature of +20°C and 65% of relative humidity)

Viscosity	3000-4000 mPas
Specific gravity	1.1
Nonvolatile	100 %
Hardening time	12 – 24 h
Color	brown

DESCRIPTION

Expansive polyurethane adhesive for wood, especially suitable for fixing loose battens in parquet floors. Can also be used as a woodworker's glue. Joints glued with PARQUET FIX offer a good resistance against humidity and solvents.

PACKAGING

0.5-Kg plastic bottle with spout.

DIRECTIONS FOR USE

PARQUET: Make a hole in the batten you have to fix and pour the glue in using the bottle spout. Leave a weight for 12 – 24 hours on the batten, then fill the hole using one of our filler bonding agents or a plastic filler, to avoid possible interaction with the finish products. Parquet may then be sanded.

JOINERY: Spread the glue with a spatula only on one surface, then clamp the two pieces to be glued for 12 – 24 hours.

ADVICE

Application should be made at a room temperature of at least +5 °C.

Glue residuals or leakage can be eliminated by:

- Using our thinner DILUENTE V3a before the hardening.
- Using a scraper or a knife after the hardening.

Be careful! PARQUET FIX may interact with the finish products.

For professional use only!

Do not dispose of residual on ground or down drains!

If the original unopened container is stored at a temperature between + 5 and 25°C, the product will keep for at least 12 months.

N.B. The information contained in this technical leaflet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.